

2MP LPR BULLET CAMERA



ENC-HBU5M-35R-75

FEATURES

License Plate Detection
Smart IR up to 35 m
ONVIF Profile (S, G, T, M)
Triple Stream
Audio and Alarm Support
PoE+, IP67



SPECIFICATION

MODEL	Model No.	ENC-HBU5M-35R-75
	Type	2MP LPR BULLET CAMERA
CAMERA	Image Sensor	1/2.8 CMOS Progressive 2.0 MegaPixel
	Day / Night Mode	Day / Night/ Schedule/ Customize/ Auto
	Lens Type	Motorized
	Focal Length	5 ~ 60 mm
	Optical Zoom	12x
	Focus	Auto / Manual
	Iris	Auto
	Lens Mount	Φ14
	Angle of View (H)	55.6° ~ 5.0°
	Angle of View (V)	32.7° ~ 2.8°
	Angle of View (D)	64.5° ~ 5.7°
	Aperture	F1.6 ~ F2.8
	Electronic Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.005 lux @ F1.6, B/W: 0 lux with IR
	AGC	Auto / Manual
	Digital Noise Reduction	2D/3D DNR
	S/N Ratio	≥55 dB
	Defog	Smart Defog
	WDR	120 dB
	Smart IR	Up to 35 m

★Product specification and availability are subject to change without notice.

2MP LPR BULLET CAMERA



ENC-HBU5M-35R-75


MODEL	Model No.	ENC-HBU5M-35R-75
	Type	2MP LPR BULLET CAMERA
VIDEO	Max. Resolution	1920x1080
	Video Compression	Enhanced (H.265, H.264), H.265, H.264, MJPEG
	Frame Rate	Main Stream: (1920x1080, 1280x960, 1280x720, 704x576) @ 90fps Sub Stream: (704x576, 640x480, 640x360, 352x288, 320x240) @ 50/60fps Third Stream: (1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240) @ 25/30fps
	Stream Settings	I-Frame, PAL/NTSC, Frame Rate
	Video Bit Rate	16 Kbps ~ 16 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness
	White Balance	Auto, Sunshine, Warm Light, Incandescent Lamp, Fluorescent Lamp, Nature Light, Manual
	Corridor Mode	Supported
	HLC	Supported
	BLC	Supported
	Image Restoration	Supported
	OSD	Supported
	OSD Type	Title, Time, Text with Different Color & Font
	Watermark	Supported
	ROI	Up to 8 regions
	Privacy Mask	Up to 8 regions (Mask area / Mosaic area)
AUDIO	Audio Compression	G.711A, G.711U, AAC, G.722, G.726
	Audio Bit Rate	16 kbps ~ 256 kbps
	Audio I/O	1/1
	Two-way Audio	Supported
SMART	Road Traffic Control	Lane Management, Evidence Camera Linkage
	Max. Vehicle Speed	120 km/h
	Accuracy	97%
	Coverage	Support detection of 4 regions simultaneously
	Identification	Vehicle Brand, Type & Color, Number Plate Color, No License Plate Vehicle Capture, Speed & Direction Detection of Vehicle, Traffic Flow Monitoring
	White / Black List	Supported (up to 20,000 records in the camera)
	Smart Search	LPR Smart Search
	Alarm Management	Motion Detection, IP Conflict, Attributes Event, White/Black List, External Input, Audio Alarm
	Alarm Notifications	FTP & SMTP Upload, HTTP Notification, White LED, SIP Phone, SD Card Record, External Output
	Protocols	TCP/IP, UDP, IPv4, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, RTMP, PPPoE, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, ARP, SNMP, SSL, SIP, VLAN, Bonjour
INTERFACE	Compatibility	ONVIF Profile (S, G, T, M), API
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Alarm I/O	1/1
	SIP/VoIP	Voice & Video-over-IP
	Edge Storage	SD card slot, up to 1TB
	ANR	Supported
	Cable Interface	Pig Tail
GENERAL	Power Supply	12V DC, PoE+ (IEEE 802.3at)
	Max. Power Consumption	≤14 W
	Working Temperature	-40 °C ~ 60 °C
	Working Humidity	≤95% RH (non-condensing)
	Ingress Protection	IP67
	Vandal Resistant	IK10
	Surge Protection	TVS4000V
	Reset Button	Supported
	Dimensions	320x134x98 mm
	Net Weight	1.6 kg

2MP LPR BULLET CAMERA



ENC-HBU5M-35R-75

Dimension Unit : mm



ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HBU5M-35R-75	2MP IR IP H.265 Bullet Camera with 5 ~ 60mm Motorized Lens, LPR, PoE, WDR, SD Card Slot and 35m IR Support	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HBU5M-35R-75	Carton Box	-	-

★Product specification and availability are subject to change without notice.